

# NOCHAR'SA611 FACT SHEET

## APPLICATION:

Dry powder material for use to immobilize petroleum-based liquids (on water or land) including fuels, solvents, paints, etc. The product is suitable to bond or congeal a spill to slow or stop the spread of the liquid.

**APPLICATION** The product is ideally suited for spill clean ups, transforming and fluids to a

removable solid with minimal  
**RECOMMENDED RATE:**

liquids volumetric increase. The amount of product to be used depends on the desired results (i.e., from congealing to solidification). Rate may vary with viscosity the

The application of the liquid being picked up. To fully solidify liquid normally requires one (1) pound of A610 to fifteen (15) pounds of spilled liquid. Test on small sample for predictable rate usage. Pick up ratio and speed of solidification

will vary with type of liquid being bonded, amount of volatiles remaining, temperatures of the liquid.

and the viscosity

**SPECIFIC WEIGHT:** 18 lbs. per

cubic foot

**WEIGHT BY VOLUME:**

One (1) pound equals (96) cubic inches.

**SPECIFIC GRAVITY:**

**FLASH POINT:** N/A

**PH SPECIFICATIONS:** Neutral (6.5) to

(7)

**TOXICITY:** This product is non-toxic, non-hazardous, see Material Safety Data Sheet

non-corrosive,

**TYPES OF MATERIAL TO BE TREATED:**

Petroleum-based liquids and solvents. Not suitable for some acids. Before application, users should test applicability of product in small samples of the spilled liquid to determine the suitability and/or application rate needed.

A610 FACT SHEET-PAGE TWO

**STORAGE SPECIFICATIONS:** Keep free of

contamination.

**VOLATILITY BEFORE USE:** None

**VOLATILITYAFTERUSE:**Varieswith the flammabilityof the liquid beingbonded.

**TESTINGREFERENCE:**Theproducthasbeen field testedanddemonstrated flammable liquidchemicals.

on various and hazardous Information

availableuponrequest.

**PACKAGING:**

Theproductmay be packagedin assorted sizesand containers dependingon the desire or need of the user. Standardpackagngis 40 pounddrums.

**METHOD OF DISPOSAL:**

Extremecautionmust be exercisedwhenhandling, storinganddisposingof solidified orgelledhazardous materials.**COMPLIANCE:** orgelledmaterials of in accordance with federal, state

Solidified must be disposed and local laws and regulations. The user issolelyresponsiblefor compliance withdisposalof solidified or gelledmaterials.

**PERFORMANCECHARACTERISTICS:**

Theproductis non-toxic, non-hazardous,non-corrosive.A6'10 should beused to control leaks and spills on eitherdry surfaces or water.