

NOCHAR'S A610 FACT SHEET

APPLICATION:

Dry powder material for use to immobilize petroleum based liquids (on water land) including fuels, solvents, paints, etc. The product is suitable to bond or congeal a spill to slow or stop the spread of the liquid.

RECOMMENDED APPLICATION RATE:

This product is ideally suited for spill clean ups, transforming liquids into a solid with a minimal volume increase. The amount of product to be used depends on the desired results (from congealing to solidification). Rate may vary with viscosity the

The application of the liquid being picked up. To fully solidify liquid normally requires one (1) pound of 4610 to fifteen (15) pounds of spilled liquid. Test a small sample for predictable rate usage. Pick up ratio and speed of solidification will vary with type of liquid being bonded and the amount of volatiles in the liquid.

SPECIFIC WEIGHT:

18 lbs. WEIGHT BY VOLUME:

One (1) pound equals (96) cubic inches

SPECIFIC GRAVITY:

1.4

FLASH POINT:

N/A

PH SPECIFICATIONS:

Neutral (6.5) to (7)

TOXICITY:

This product is non-toxic, non-hazardous, non-corrosive,

TYPES OF MATERIAL TO BE TREATED:

Petroleum-based liquid and solvents. Not suitable for some acids. Before application, user should test applicability with small samples of the spilled liquid to determine the suitability and/or application rate needed

A610FACTSHEET-PAGETWO

STORAGE SPECIFICATIONS:

Keep free of contamination.

VOLATILITY BEFORE USE

: None

PERFORMANCE CHARACTERISTICS:

This product is non-toxic, non-hazardous, and non-corrosive. A610 should be used to control leaks and spills on either dry surfaces or water.